

This Conference Control Host is recommended for compatibility with AVFI's **T48-LFT15** Monitor Lift's microphone.



Specifications

- The control panel adopts LCD screen to display system settings and working status. More intuitive and user-friendly.
- Multiple operating modes: Limit mode/First-in-First-out (FIFO) mode.
- Equipped with background music volume and total volume output regulator.
- Built-in telephone coupling input and output ports, which can be used for remote teleconferencing.
- Each system host can be connected to 60 microphone units in three parallel outputs.
- With 'first-in-first-out' / 'full open' / 'restricted' multiple speech modes.
- Limit mode has a limit switch for the number of microphones working at the same time, selectable '1' or '3'.
- Equipped with audio parallel output and 6.3 jack output connector.
- Audio parallel output and 6.3 jack output interface.
- Conference process recording output function interface
- Rated voltage: AC220V $\pm$ 10% 50Hz
- Frequency Response: 100Hz-12.5KHz
- Output impedance: REC: 200 Ω
 LINE: 200 Ω
 BALANCE: 300 Ω
 NO BALANCE: 400 Ω
- Input Impedance: LINE:50K Ω ,PBIN:50K Ω
- Signal-to-noise ratio: 78dB (1KHz THD1%)
- 19' International Standard Rack
- Maximum size: 485x220x66MM

External Power Supply: AC 110V

Certifications: CE

1 year warranty.

The information contained in this drawing is the sole property of Audio Visual Furniture International. Any reproduction in part or as a whole without the written permission of Audio Visual Furniture International is prohibited. We can build or modify stock configurations to suit customer specifications. Please contact us to discuss how this service can help meet your needs. Some quantity restrictions may apply. Specification subject to change without notice. Computers, cameras, monitors, etc. are shown to illustrate product usage and are not included unless otherwise noted.